

LIFTING TABLE 1000kg FOR EV BATTERY AND HEAVY ORGANS

Reference : OH 1301



Item name	LIFTING TABLE 1000kg FOR EV BATTERY AND HEAVY ORGANS
Bar code	3700461499470
Introduction	<p>This table is specially designed for the removal and re-installation of heavy components with a maximum load of 1T (electric vehicle battery and/or drive train). Versatile, it will be able to adapt to all your needs thanks to its many adjustments and its optional supports on request.</p>
Text	<p>A hydropneumatic control allows effortless, fast and precise height control. The descent is secured by the "dead man" function which requires 2 simultaneous actions of the operator. This function will be automatically stopped in case of problem concerning the operator. The platform is fully mobile in relation to its frame and has 104 M10x1.5 drilled and tapped points, which can be used to receive various accessories (available on request).</p>
Product highlight	Precision and maneuverability
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- length: 1680mm- width: 780mm- height: 1000mm- minimum tray height: 725mm- maximum height of the tray: 1995mm- maximum shelf length: 1560mm- minimum tray length: 1340mm- climb time: +/-60s

- descent time: +/-20s
- 4 swivel braking wheels: 130mm
- 4 handles place around the table for optimal ease of use when adjusting the load to the stand.
- weight: 385kg

Adjustments :

- the tray is deployed in three lockable positions for a max. area of 1560mmx730mm. It is tapped M10x1.5 to receive different accessories (available on request).
- table flatness is adjustable in 2 points for high positioning accuracy (tilt degree +/- 20%)
- the tray is movable in translation and swivelable for greater precision during the element support.

Contents

Contents:

Delivered in 4 packages to be mounted

- package n°1 : mounted lifting table
- package n°2 : 4 swivel wheels, 4 tray handles, 2 control cables for descent release, 1 pump support, screws and assembly instructions.
- package n°3 : handle frame and screws
- package n°4 : pump, hydraulic hose and seals.

Options

Option:

- screwable supports (ex: CO1160)

Warranty period

2 years

Length (mm)

1,680.00 mm

Width

785.00 mm

Height

1,000.00 mm

Product weight (kg)

385.00 kg

Max. height

1,995.00 mm

Min. height

725.00 mm

Maximum load (T)

1.00 T

Tariff code

Tariff Equipment (TE)

Warranty Procedure

DIAGNOSTIC

Customer benefit

Supports for forklift pickup.
Suitable for precision use.



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)