

AUTOMATIC TIRE CHANGER 10"-24" 1 SPEED SYSTEM 230V

Reference: DM 1522



Item name AUTOMATIC TIRE CHANGER 10"-24" 1 SPEED SYSTEM 230V

EAN code 3700461402609

Intro 1-speed automatic tire changer with mounting aid (assistance arm)

Automatic tire changer specially adapted for the effortless mounting and dismounting of

all car, utility and 4x4 tires.

Equipped with the bead pusher device with articulated bead pusher arm, adjustable to fit

to each type of rim and tires.

Text For warranty purposes, installation and set-up must be performed by a professional.

Product highlight Versatile

Specifications Specifications:

- horizontal arm on roller for easy movement

- inflator with pressure gauge

- maximum tire diameter: 1180mm

- max. tire width: 3 to 12 inches

- arched platform with anti-pinch safety device

- outside rim diameter: 10 to 21 inches - inner rim diameter: 12 to 24 inches

- 1 speed without switch: rotation speed 1: 6.5 rpm

- ergonomic, intuitive pedals

- 2-position adjustable bead breaker shovel and double-acting cylinder

- operating pressure: 8-10bar - air cleaner and oil lubricator - tubeless inflation safety valve: 3.5bar

- noise < 70dB

power supply: 230Vpower: 0.75kW

bead breaker power: 2500kgtire changer weight: 315kg

- dimensions: 1850x1800x1980mm

Contents Comes with:

SA8902: 5 protection padsSA8903: 5 protective clips

- SA8904: 1 blade protection cover 260x80mm

SA8906: 4 pieces jaw cover set1 lever with protection for alu rims

Options Options:

- DM1102: dual head quick fastening connection for alu/steel

Warranty period 2 years

Power 750W

Tension 240V

Length 1,850.00 mm

Width 1,800.00 mm

Height 1,980.00 mm

Product weight 315.00 kg

Tariff code Tariff Equipment (TE)

Warranty Procedure INTERVENTION











*Public price Exl. Tax : €4,299.00

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)