

AUTOMATIC TIRE CHANGER 10"-24" 1 SPEED SYSTEM 230V

Reference : DM 1522



Item name	AUTOMATIC TIRE CHANGER 10"-24" 1 SPEED SYSTEM 230V
EAN code	3700461402609
Intro	<p>1-speed automatic tire changer with mounting aid (assistance arm) Automatic tire changer specially adapted for the effortless mounting and dismounting of all car, utility and 4x4 tires. Equipped with the bead pusher device with articulated bead pusher arm, adjustable to fit to each type of rim and tires.</p>
Text	For warranty purposes, installation and set-up must be performed by a professional.
Product highlight	Versatile
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- horizontal arm on roller for easy movement- inflator with pressure gauge- maximum tire diameter: 1180mm- max. tire width: 3 to 12 inches- arched platform with anti-pinch safety device- outside rim diameter: 10 to 21 inches- inner rim diameter: 12 to 24 inches- 1 speed without switch: rotation speed 1: 6.5 rpm- ergonomic, intuitive pedals- 2-position adjustable bead breaker shovel- operating pressure: 8-10bar- air cleaner and oil lubricator

- tubeless inflation safety valve: 3.5bar
- noise < 70dB
- power supply: 230V
- power: 0.75kW
- bead breaker power: 2500kg
- tire changer weight: 315kg
- dimensions: 1850x1800x1980mm

Contents

Comes with:

- SA8902: 5 protection pads
- SA8903: 5 protective clips
- SA8904: 1 blade protection cover 260x80mm
- SA8906: 4 pieces jaw cover set
- 1 lever with protection for alu rims

Options

Options:

- DM1102: dual head quick fastening connection for alu/steel

Warranty period 2 years

Power 750W

Tension 240V

Length 1,850.00 mm

Width 1,800.00 mm

Height 1,980.00 mm

Product weight 315.00 kg

Tariff code Tariff Equipment (TE)

Warranty Procedure INTERVENTION



***Public price Exl. Tax : €4,299.00**

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)