

## PNEUMATIC SPRING COMPRESSOR 4T

Reference : OP 3241



<b>Item name</b>	PNEUMATIC SPRING COMPRESSOR 4T
<b>EAN code</b>	3701555300085
<b>Intro</b>	<p>Specially designed to fit and hold McPherson shock absorber springs thanks to the innovative articulation system of the lower cup allowing the positioning of left or right angular spiral, it covers springs from Ø78 to Ø205mm.</p> <p>This retractable cup also allows the locking by the strut in vice grip Ø75mm.</p> <p>The spring is compressed by the positioning of 2 articulated jaws, mounted on 2 free arms which naturally follow the spring's turn.</p>
<b>Product highlight</b>	<p>Conformity 2006/42CE</p> <p>Compatible with electric vehicles</p>
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- compression force : 4000kg</li><li>- stroke : 380mm</li><li>- integral protection grid lined with high resistance polycarbonate plexiglass</li><li>- pneumatic safety at the opening of the grid and at the pedal control</li><li>- working pressure : 8bar/maxi 10bar</li><li>- conformity 2006/42CE</li><li>- dimensions: H.1731xL.957xW.625mm</li><li>- weight: 110kg</li></ul>
<b>Contents</b>	<p>Content:</p> <ul style="list-style-type: none"><li>- OP2003: articulated jaws</li><li>- SA6906: fall arrest support</li></ul>

<b>Applications</b>	Thermal, electric, hybrid vehicles, bulletproof vehicles, utility vehicles, SUV, 4X4, ambulances... covers springs from Ø78 to Ø205mm.
<b>Warranty period</b>	5 years
<b>Product weight</b>	110.00 kg
<b>Maximum load (T)</b>	4.00 T
<b>Tariff code</b>	Tariff Normal (TN)
<b>Product range</b>	Approved by SNR
<b>Warranty Procedure</b>	DIAGNOSTIC



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to  
12h30 and from 14h to 17h30  
(16h30 on Friday)