

## GAS SUCTION UNIT REGENERATION DPF 5m Ø150mm 230V

Reference : AG 0057



**Item name** GAS SUCTION UNIT REGENERATION DPF 5m Ø150mm 230V

**EAN code** 3701555301464

**Intro** Specific kit for the LV DPF regeneration.

**Text** Individual mini kit with funnel on TUV certified trolley for exhaust gas suction in high temperature conditions (particulate filter regeneration).  
The equipment allows to work in a healthy environment without inhalation of exhaust gases and in compliance with the safety standards at work.  
Flexible hose made of two-layer fiberglass fabric with an outer spiral made of steel wire covered with another strip of protective fabric.  
Seamless inner surface and Kevlar coating for added durability.  
End sleeves for easy connection.

**Product highlight** High temperature

**Specifications** Specifications:  
- galvanized steel structure  
- epoxy paint (grey RAL 7040)  
- length of pipe: 5m resistant 500° Ø 150mm  
- delivery: Ø 160mm  
- power supply: 230V Mono  
- motor power: 1,5cv, 1,1KW, 50HZ, 4,2A  
- max flow: 1200m<sup>3</sup>/h  
- noise level: 72dB  
- thermal protection switch

Many options available, please consult us.

<b>Warranty period</b>	2 years
<b>Vehicle type</b>	LV
<b>Decibel level</b>	72.00 dB
<b>Tension</b>	240V
<b>Cable length</b>	5.00 m
<b>Diameter</b>	150.00 mm
<b>Air flow rate</b>	1200
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Type of gas extraction system</b>	Fixed
<b>DPF compatible</b>	YES
<b>Hose length (m)</b>	5m
<b>Hose diameter (mm)</b>	150mm
<b>Max. hose temperature (°C)</b>	500°C



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)