

## EXHAUST GAS ON ROLLER MOTORCYCLE 15m Ø75mm HIGH PRESSURE

Reference : AG 0005



**Item name** EXHAUST GAS ON ROLLER MOTORCYCLE 15m Ø75mm HIGH PRESSURE

**Bar code** 3701555300948

**Introduction** Specially designed for exhaust extraction in motorcycle workshops.

**Text** This mechanical spring reel complete with exhaust blower can be installed on the ceiling or wall, always maintaining the same performance. The equipment allows you to work in a healthy environment without inhalation of exhaust gases and in compliance with work safety standards.

Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from collapsing in high stress situations. Its smooth design on the inside guarantees maximum suction efficiency in m3.

Directly coupled electric motor, statically and dynamically balanced impeller to limit friction, vibration and reduce energy consumption. Inlet and outlet flanges are sized for optimum suction capacity. Support feet for wall or ceiling mounting are included.

**Product highlight** Large flow

**Specifications** Specifications:

- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 10m of pipe Ø75mm (-40° to +200°) in high temperature EPDM vulcanized fabric on both sides
- delivery: Ø125mm
- power supply: 230V Mono

- engine power: 0.5hp, 0.35KW, 50HZ, 1.7A
- max flow: 450m3/h
- noise level: 66dB
- thermal protection switch
- reel equipped with a ratchet, an end stop with anti-skid system
- exhaust nozzle equipped with an anti-intrusion grid, a vice grip, a gas suction shutter and an access for the opacimeter probe
- weight: 43kg

Many options available, please contact us.

<b>Warranty period</b>	2 years
<b>Vehicle type</b>	Moto
<b>Decibel level</b>	66.00 dB
<b>Voltage</b>	240V
<b>Cable length</b>	15.00 m
<b>Product weight (kg)</b>	43.00 kg
<b>Diameter (mm)</b>	75.00 mm
<b>Air flow rate</b>	450
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Type of gas extraction system</b>	Fixed
<b>DPF compatible</b>	NO
<b>Hose length (m)</b>	12m
<b>Hose diameter (mm)</b>	75mm
<b>Max. hose temperature (°C)</b>	200°C



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)