

## **EXHAUST GAS ON ROLL HEAVY WEIGHT 10m Ø125mm 400V**

Reference: AG 0012



Item name EXHAUST GAS ON ROLL HEAVY WEIGHT 10m Ø125mm 400V

**Bar code** 3701555301013

**Introduction** Specially designed for exhaust gas suction for HGV workshops.

**Text** This mechanical spring reel complete with exhaust blower can be installed on the ceiling or wall, always maintaining the same performance. The equipment allows you to work in

a healthy environment without inhalation of exhaust gases and in compliance with work

safety standards.

Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from collapsing in high stress situations. Its smooth design on the inside guarantees

maximum suction efficiency in m3.

Directly coupled electric motor, statically and dynamically balanced impeller to limit friction, vibration and reduce energy consumption. Inlet and outlet flanges are sized for optimum suction capacity. Support feet for wall or ceiling mounting are included.

## **Specifications**

## **Specifications:**

- galvanized steel structure

- epoxy paint (grey RAL 7040)

- 10m of pipe  $\emptyset$ 125mm (-40° to +200°) in high temperature EPDM vulcanized fabric on

both sides

- delivery: Ø125mm

- power supply: 400V Tri

- engine power: 0.5hp, 0.37KW, 50HZ, 1.0A

max flow: 450m3/hnoise level: 66dB

- thermal protection switch

- reel equipped with a ratchet, an end stop with anti-skid system

- exhaust nozzle equipped with an anti-intrusion grid, a vice grip, a gas suction shutter and

an access for the opacimeter probe

- weight: 56kg

Many options available, please contact us.

Warranty period 2 years

Vehicle type HGV

**Decibel level** 68.00 dB

Voltage 400V

Product weight (kg) 56.00 kg

**Diameter (mm)** 125.00 mm

Air flow rate 700

**Tariff code** Tariff Equipment (TE)

**Type of gas** Fixed

extraction system

**DPF compatible** NO

**Hose length (m)** 10m

Hose diameter (mm) 125mm

Max. hose 200°C

temperature (°C)







