

EXHAUST GAS ON ROLL 15m Ø125mm 400V

Reference: AG 0014



Item name EXHAUST GAS ON ROLL 15m Ø125mm 400V

Bar code 3701555301037

Introduction Specially designed for exhaust gas suction for LV workshops.

Text This mechanical spring reel complete with exhaust blower can be installed on the ceiling

or wall, always maintaining the same performance. The equipment allows you to work in a healthy environment without inhalation of exhaust gases and in compliance with work

safety standards.

Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from collapsing in high stress situations. Its smooth design on the inside guarantees

maximum suction efficiency in m3.

Directly coupled electric motor, statically and dynamically balanced impeller to limit friction, vibration and reduce energy consumption. Inlet and outlet flanges are sized for optimum suction capacity. Support feet for wall or ceiling mounting are included.

Specifications

Specifications:

- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 15m of pipe Ø125mm (-40° to +200°) in high temperature EPDM vulcanized fabric on both sides
- delivery: Ø160mm
- power supply: 400V Tri
- engine power: 1.0hp, 0.75KW, 50HZ, 1.7A

max flow: 700m3/hnoise level: 68dB

- thermal protection switch

- reel equipped with a ratchet, an end stop with anti-skid system

Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30

and from 14h to 17h30 (16h30 on

Friday)

- exhaust nozzle equipped with an anti-intrusion grid, a vice grip, a gas suction shutter and

an access for the opacimeter probe

- weight: 43kg

Many options available, please contact us.

Warranty period 2 years

Vehicle type LV

Decibel level 68.00 dB

Voltage 400V

Product weight (kg) 43.00 kg

Diameter (mm) 125.00 mm

Air flow rate 700

Tariff code Tariff Equipment (TE)

Type of gas Fixed

extraction system

DPF compatible NO

Hose length (m) 12m

Hose diameter (mm) 125mm

Max. hose 200°C

temperature (°C)







