

EXHAUST GAS ON ROLL HEAVY WEIGHTS 10m Ø150mm 400V

Reference : AG 0015



Item name EXHAUST GAS ON ROLL HEAVY WEIGHTS 10m Ø150mm 400V

EAN code 3701555301044

Intro Specially designed for exhaust gas suction for HGV workshops.

Text This mechanical spring reel complete with exhaust blower can be installed on the ceiling or wall, always maintaining the same performance. The equipment allows you to work in a healthy environment without inhalation of exhaust gases and in compliance with work safety standards.
Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from collapsing in high stress situations. Its smooth design on the inside guarantees maximum suction efficiency in m3.
Directly coupled electric motor, statically and dynamically balanced impeller to limit friction, vibration and reduce energy consumption. Inlet and outlet flanges are sized for optimum suction capacity. Support feet for wall or ceiling mounting are included.

Specifications Specifications:
- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 10m Ø150mm pipe (-40° to +200°) in high-temperature EPDM vulcanized fabric on both sides
- discharge: Ø 160mm
- power supply: 400 Tri
- motor power: 1.0hp, 0.75KW, 50HZ, 1.7A

- max flow: 1000m³/h
- noise level: 68dB
- thermally protected switch
- metal flanges
- reel equipped with ratchet, end-stop and anti-slip system
- exhaust nozzle equipped with anti-intrusion grid, vice grip, gas suction shut-off flap and access for opacimeter probe
- weight: 73kg

Numerous options available on request.

| | |
|--------------------------------------|---|
| Warranty period | 2 years |
| Vehicle type | HGV |
| Decibel level | 68.00 dB |
| Tension | 400V |
| Product weight | 73.00 kg |
| Diameter | 150.00 mm |
| Air flow rate | 1000 |
| Tariff code | Tariff Equipment (TE) |
| Type of gas extraction system | Fixed |
| DPF compatible | NO |
| Hose length (m) | 10m |
| Hose diameter (mm) | 150mm |
| Max. hose temperature (°C) | 200°C |
| Customer benefit | Connection of the hose to the reel by an ABS gooseneck, guarantees no deformation, no loss of suction efficiency. |



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)