

SINGLE EXTRACTOR GROUP 5m Ø100mm 400V

Reference: AG 0020



Item name SINGLE EXTRACTOR GROUP 5m Ø100mm 400V

EAN code 3701555301099

Intro Specially designed for exhaust extraction in light vehicle workshops.

Suitable for wall or roof extraction, depending on accessories.

Text The equipment enables you to work in a healthy environment, without inhaling exhaust

fumes and in compliance with workplace safety standards.

Product highlight Easy to install

Specifications Specifications:

- galvanized steel structure
- electric motor, statically and dynamically balanced wheel, delivered with wall bracket and rubber funnel.
- 5m of $\emptyset 100$ mm hose (-40° to +200°) made of high temperature EPDM vulcanized fabric on both sides. Completely anti-crushing structure, smooth inside and maintains flexibility over time thanks to the strong nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from crushing in high stress situations.

- delivery: Ø 125mm - power supply: 400V Tri

- motor power: 0,5cv, 0,37KW, 50HZ, 1.0A

- max flow: 450m3/h - noise level: 66dB

- thermal protection switch

- rubber exhaust nozzle with watertight valve included in the body of the product, antiintrusion network, clamp for fixing to the exhaust

Many options available, please consult us.

Warranty period 2 years

Vehicle type LV

Decibel level 66.00 dB

Tension 400V

Diameter 100.00 mm

Air flow rate 450

Tariff code Tariff Equipment (TE)

Type of gas Fixed

extraction system

DPF compatible NO

Hose length (m) 5m

Hose diameter (mm) 100mm

Max. hose 200°C

temperature (°C)









CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)