

DOUBLE EXTRACTOR GROUP 2x5m Ø100mm

Reference : AG 0021



Item name	DOUBLE EXTRACTOR GROUP 2x5m Ø100mm
Bar code	3701555301105
Introduction	Specially designed for exhaust extraction in light vehicle workshops. Suitable for wall or roof extraction, depending on accessories.
Text	The equipment enables you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.
Product highlight	Easy to install
Specifications	Specifications: <ul style="list-style-type: none">- galvanized steel structure- electric motor, statically and dynamically balanced wheel, delivered with wall bracket and rubber funnel.- 2x5m of hose Ø100mm (-40° to +200°) in high temperature EPDM vulcanized fabric on both sides. Completely anti-crushing structure, smooth inside and maintains flexibility over time thanks to the strong nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from crushing in high stress situations.- delivery: Ø 125mm- power supply: 230V Mono- motor power: 1hp, 0,75KW, 50HZ, 2,9A- max flow: 450m³/h- noise level: 66dB- thermal protection switch- rubber exhaust nozzle with watertight valve included in the body of the product, anti-

intrusion network, clamp for fixing to the exhaust

Many options available, please consult us.

Warranty period	2 years
Vehicle type	LV
Decibel level	66.00 dB
Voltage	240V
Diameter (mm)	100.00 mm
Air flow rate	2X450
Tariff code	Tariff Equipment (TE)
Type of gas extraction system	Fixed
DPF compatible	NO
Hose length (m)	2 x 5m
Hose diameter (mm)	100mm
Max. hose temperature (°C)	200°C



***Public price Exl. Tax : €2,469.00**

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)