

## DOUBLE EXTRACTOR GROUP 2x5m Ø100mm 400V

Reference : AG 0022



**Item name** DOUBLE EXTRACTOR GROUP 2x5m Ø100mm 400V

**Bar code** 3701555301112

**Introduction** Specially designed for exhaust extraction in light vehicle workshops.  
Suitable for wall or roof extraction, depending on accessories.

**Text** The equipment enables you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.

**Product highlight** Easy to install

**Specifications** Specifications:

- galvanized steel structure
- electric engine, statically and dynamically balanced wheel, delivered with wall bracket and rubber funnel
- 2x5m of Ø100mm hose (-40° to +200°) made of high temperature EPDM vulcanized fabric on both sides. Completely anti-crushing structure, smooth inside and maintains flexibility over time thanks to the strong nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from crushing in high stress situations.
- delivery: Ø125mm
- power supply: 400V Tri
- engine power: 1hp, 0.75KW, 50HZ, 2.9A
- max flow: 2x450m<sup>3</sup>/h
- noise level: 66dB
- thermal protection switch

- rubber exhaust nozzle with watertight valve included in the body of the product, anti-intrusion network, clamp for fixing to the exhaust

Many options available, please consult us.

<b>Warranty period</b>	2 years
<b>Vehicle type</b>	LV
<b>Decibel level</b>	66.00 dB
<b>Voltage</b>	400V
<b>Diameter (mm)</b>	100.00 mm
<b>Air flow rate</b>	2X450
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Type of gas extraction system</b>	Fixed
<b>DPF compatible</b>	NO
<b>Hose length (m)</b>	2 x 5m
<b>Hose diameter (mm)</b>	100mm
<b>Max. hose temperature (°C)</b>	200°C



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)