

DOUBLE GAS MOBILE VACUUM 2x1.25m Ø75mm

Reference: AG 0023



Item name DOUBLE GAS MOBILE VACUUM 2x1.25m Ø75mm

EAN code 3701555301129

Intro Perfect for moving to different work areas for the LV workshops.

Text Trolley extractor mounted on 4 swivel wheels, adjustable in height, it is equipped with a

Y and 1.25m hoses with exhaust tips fitted with clamps as well as a delivery sheath and a

storage console.

The equipment allows to work in a healthy environment without inhalation of exhaust

gases and in compliance with the safety standards at work.

Product highlight Mobility

Specifications Specifications:

- galvanized steel structure

- the platform is mounted on 4 swivel wheels to ensure anti-tilt stability

- epoxy paint (grey RAL 7040)

- 2x1.25m of Ø75mm (-40° to +200°) high-temperature EPDM vulcanized fabric tubing.

- discharge: Ø 125mm length 5m

- power supply: 230V Mono

- motor power: 0.5hp, 0.37KW, 50HZ, 1.7A

- max flow: 2X250m3/h

- noise level: 66dB

- on/off switch

- exhaust nozzles equipped with anti-intrusion grid, manual clamps, suction shut-off

flaps, for optimized suction on one mouth with access for opacimeter probe

Warranty period 2 years

Vehicle type LV

Decibel level 66.00 dB

Tension 240V

More Products with electrical plug

Diameter 75.00 mm

Air flow rate 2x250

Tariff code Tariff Equipment (TE)

Type of gas Mobile

extraction system

DPF compatible NO

Hose length (m) $2 \times 1.25 \text{m}$

Hose diameter (mm) 75mm

Max. hose 200°C

temperature (°C)







CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)