

## DOUBLE GAS MOBILE VACUUM 2x1.25m Ø75mm

Reference : AG 0023



**Item name** DOUBLE GAS MOBILE VACUUM 2x1.25m Ø75mm

**Bar code** 3701555301129

**Introduction** Perfect for moving to different work areas for the LV workshops.

**Text** Trolley extractor mounted on 4 swivel wheels, adjustable in height, it is equipped with a Y and 1.25m hoses with exhaust tips fitted with clamps as well as a delivery sheath and a storage console.  
The equipment allows to work in a healthy environment without inhalation of exhaust gases and in compliance with the safety standards at work.

**Product highlight** Mobility

**Specifications** Specifications:

- galvanized steel structure
- the platform is mounted on 4 swivel wheels to ensure anti-tilt stability
- epoxy paint (grey RAL 7040)
- 2x1.25m of Ø75mm (-40° to +200°) high-temperature EPDM vulcanized fabric tubing.
- discharge: Ø 125mm length 5m
- power supply: 230V Mono
- motor power: 0.5hp, 0.37KW, 50HZ, 1.7A
- max flow: 2X250m<sup>3</sup>/h
- noise level: 66dB
- on/off switch
- exhaust nozzles equipped with anti-intrusion grid, manual clamps, suction shut-off flaps, for optimized suction on one mouth with access for opacimeter probe

<b>Warranty period</b>	2 years
<b>Vehicle type</b>	LV
<b>Decibel level</b>	66.00 dB
<b>Voltage</b>	240V
<b>More</b>	Products with electrical plug
<b>Diameter (mm)</b>	75.00 mm
<b>Air flow rate</b>	2x250
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Type of gas extraction system</b>	Mobile
<b>DPF compatible</b>	NO
<b>Hose length (m)</b>	2 x 1.25m
<b>Hose diameter (mm)</b>	75mm
<b>Max. hose temperature (°C)</b>	200°C



TE

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)