

DOUBLE GAS MOBILE VACUUM 2x1.25m Ø75mm

Reference : AG 0023



Item name DOUBLE GAS MOBILE VACUUM 2x1.25m Ø75mm

Bar code 3701555301129

Introduction Perfect for moving to different work areas for the LV workshops.

Text Trolley extractor mounted on 4 swivel wheels, adjustable in height, it is equipped with a Y and 1.25m hoses with exhaust tips fitted with clamps as well as a delivery sheath and a storage console.
The equipment allows to work in a healthy environment without inhalation of exhaust gases and in compliance with the safety standards at work.

Product highlight Mobility

Specifications Specifications:

- galvanized steel structure
- the platform is mounted on 4 swivel wheels to ensure anti-tilt stability
- epoxy paint (grey RAL 7040)
- 2x1.25m of Ø75mm (-40° to +200°) high-temperature EPDM vulcanized fabric tubing.
- discharge: Ø 125mm length 5m
- power supply: 230V Mono
- motor power: 0.5hp, 0.37KW, 50HZ, 1.7A
- max flow: 2X250m³/h
- noise level: 66dB
- on/off switch
- exhaust nozzles equipped with anti-intrusion grid, manual clamps, suction shut-off flaps, for optimized suction on one mouth with access for opacimeter probe

Warranty period	2 years
Vehicle type	LV
Decibel level	66.00 dB
Voltage	240V
More	Products with electrical plug
Diameter (mm)	75.00 mm
Air flow rate	2x250
Tariff code	Tariff Equipment (TE)
Type of gas extraction system	Mobile
DPF compatible	NO
Hose length (m)	2 x 1.25m
Hose diameter (mm)	75mm
Max. hose temperature (°C)	200°C



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)