

2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 230V 4T

Reference : PE 2000M



Item name	2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 230V 4T
EAN code	3701555306896
Intro	Specially designed for screeds that do not meet the minimum thickness requirements of 200mm, or have a slight flatness problem.
Text	Electro-hydraulic post lift. Push cylinder on cart, without chain. Multiple lifting capacities thanks to the telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm). Cylinder and cable protection strip included on each column.
Product highlight	Low thickness slab
Specifications	Specifications: <ul style="list-style-type: none">- lifting height: 126-1890mm- lifting time: +/- 40s- lowering time: +/- 40s- drive power: 2.2 kW- electrical voltage of the drive: (3 ~) 400/50 V/Hz- adjustable pads on 55mm stroke screw- electromagnetic unlocking of the safety notches- overload safety and hose rupture- bevelled columns for large door openings- synchronization system by cable- made in Europe

- Epoxy painting

Options

Options :

- PE0007: Mercedes/Iveco 105-135mm extension sets

Advice

Installation et mise en service, nous consulter. (ne pas installer sur une dalle d'une épaisseur à 150mm)

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period

2 years

Power

2200W

Tension

240V

Product weight

800.00 kg

Maximum load (T)

4.00 T

Tariff code

Tariff Equipment (TE)

Composition of nomenclature

1 x PE 2000M-1 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 230V 4T PACK. 1/3

1 x PE 2000M-2 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 230V 4T PACK. 2/3

1 x PE 2000M-3 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 230V 4T PACK. 3/3



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)