

2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

Reference : PE 2000T



Item name	2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T
Bar code	3701555306902
Introduction	Specially designed for screeds that do not meet the minimum thickness requirements of 200mm, or have a slight flatness problem.
Text	Electro-hydraulic post lift. Push cylinder on cart, without chain. Multiple lifting capacities thanks to the telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm). Cylinder and cable protection strip included on each column.
Product highlight	Low thickness slab
Specifications	Specifications: <ul style="list-style-type: none">- lifting height: 126-1890mm- lifting time: +/- 40s- lowering time: +/- 40s- drive power: 2.2 kW- electrical voltage of the drive: (3 ~) 400/50 V/Hz- adjustable pads on 55mm stroke screw- electromagnetic unlocking of the safety notches- overload safety and hose rupture- bevelled columns for large door openings- synchronization system by cable- made in Europe

- Epoxy painting

Options

Options :

- PE0007 : jeux de rehausses Mercedes / Iveco 105-135mm

Advice

Consult us for installation and commissioning.

Do not install on a slab less than 150mm thick.

For warranty purposes, installation and commissioning must be carried out by a professional.

Shipping costs excluded.

Warranty period 2 years

Power 2200W

Voltage 400V

Product weight (kg) 800.00 kg


Maximum load (T) 4.00 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 2000T-2 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 2/3

1 x PE 2000T-3 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 3/3

1 x PE 2000T-1 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 1/3



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)