

## 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

Reference : PE 2000T



<b>Item name</b>	2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T
<b>EAN code</b>	3701555306902
<b>Intro</b>	Specially designed for screeds that do not meet the minimum thickness requirements of 200mm, or have a slight flatness problem.
<b>Text</b>	Electro-hydraulic post lift. Push cylinder on cart, without chain. Multiple lifting capacities thanks to the telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm). Cylinder and cable protection strip included on each column.
<b>Product highlight</b>	Low thickness slab
<b>Specifications</b>	Specifications: <ul style="list-style-type: none"><li>- lifting height: 126-1890mm</li><li>- lifting time: +/- 40s</li><li>- lowering time: +/- 40s</li><li>- drive power: 2.2 kW</li><li>- electrical voltage of the drive: (3 ~) 400/50 V/Hz</li><li>- adjustable pads on 55mm stroke screw</li><li>- electromagnetic unlocking of the safety notches</li><li>- overload safety and hose rupture</li><li>- bevelled columns for large door openings</li><li>- synchronization system by cable</li><li>- made in Europe</li></ul>

- Epoxy painting

## Options

Options :

- PE0007 : jeux de rehausses Mercedes / Iveco 105-135mm

## Advice

Consult us for installation and commissioning.

Do not install on a slab less than 150mm thick.

For warranty purposes, installation and commissioning must be carried out by a professional.

Shipping costs excluded.

## Warranty period

2 years

## Power

2200W

## Tension

400V

## Product weight

800.00 kg

## Maximum load (T)

4.00 T

## Tariff code


Tariff Equipment (TE)

## Composition of nomenclature

1 x PE 2000T-2 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 2/3

1 x PE 2000T-3 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 3/3

1 x PE 2000T-1 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 1/3



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)