

2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

Reference: PE 2000T



Item name 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

Bar code 3701555306902

Introduction Specially designed for screeds that do not meet the minimum thickness requirements of

200mm, or have a slight flatness problem.

Text Electro-hydraulic post lift.

Push cylinder on cart, without chain.

Multiple lifting capacities thanks to the telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm).

Cylinder and cable protection strip included on each column.

Product highlight Low thickness slab

Specifications Specifications:

- lifting height: 126-1890mm

- lifting time: +/- 40s - lowering time: +/- 40s - drive power: 2.2 kW

- electrical voltage of the drive: (3 ~) 400/50 V/Hz

- adjustable pads on 55mm stroke screw

- electromagnetic unlocking of the safety notches

- overload safety and hose rupture

- bevelled columns for large door openings

- synchronization system by cable

- made in Europe

- Epoxy painting

Options Options:

- PE0007 : jeux de rehausses Mercedes / Iveco 105-135mm

Advice Consult us for installation and commissioning.

Do not install on a slab less than 150mm thick.

For warranty purposes, installation and commissioning must be carried out by a

professional.

Shipping costs excluded.

Warranty period 2 years

Power 2200W

400V Voltage

Product weight (kg) 800.00 kg

Maximum load (T) 4.00 T

Tariff code Tariff Equipment (TE)

Composition of 1 x PE 2000T-2 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

nomenclature PACK. 2/3

1 x PE 2000T-3 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

PACK. 3/3

PACK. 1/3

1 x PE 2000T-1 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T







400V



*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France

Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)