

## 2 COLUMNS POST LIFT 400V 6T HIGH PASSAGE 4480mm 2.6Kw

Reference : PE 2011T



<b>Item name</b>	2 COLUMNS POST LIFT 400V 6T HIGH PASSAGE 4480mm 2.6Kw
<b>Bar code</b>	3701555307046
<b>Introduction</b>	Particularly adapted to repair activities on extended utility vehicles, 4x4, micro car.
<b>Text</b>	<p>Electro-hydraulic post lift.</p> <p>Hoses and cables pass through the top for optimal working comfort, allowing free access under the vehicle for equipment (jacks, oil recuperator...), making it easier to clean the workshop.</p> <p>Hydraulic unit: quick up and down with adjustment possibility, equipped with a position securing device for precise intervention, gearbox assembly, nut alignment...</p> <p>Multiple lifting capacities thanks to the articulated arms in symmetrical version (3 stages from 790 to 1890mm) allowing lifting adjustable to the millimeter of vehicles.</p> <p>Adjustable pads on 55mm stroke screw equipped with 70mm and 160mm extensions.</p> <p>Electromagnetic unlocking of the safety notches, overload safety and hose rupture.</p> <p>Hydraulic synchronization system.</p> <p>Particularly suitable for repair activities on extended commercial vehicles, 4x4, micro cars.</p> <p>Made in Europe, powder coated.</p>
<b>Product highlight</b>	Large scope of application
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height : 100-1920mm</li><li>- lifting time : +/- 80s</li><li>- lowering time : +/- 100s</li></ul>

- driving power: 2.6kW
- drive voltage: (3 ~) 400/50 V/Hz
- concrete strength/quality: 200mm-C20/25
- adjustable buffers on screw 55mm stroke (+ raised 70 and 160mm)
- electro-magnetic unlocking of the safety notches
- bevelled columns for large door openings
- overload and hose rupture safety
- semi-automatic hydraulic system synchronization
- made in Europe
- Epoxy painting

### Options

Options :

- PE0007 : Jeux de rehausses Mercedes / Iveco 105-135mm

### Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

### Warranty period

2 years

### Power

2600W

### Voltage

400V

### Product weight (kg)

1,310.00 kg

### Maximum load (T)

6.00 T

### Tariff code

Tariff Equipment (TE)

### Composition of nomenclature

1 x PE 2011T-1 - 2 COLUMNS POST LIFT 400V 6T HIGH PASSAGE 5080mm 2.6Kw  
PACK. 1/1



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)