

DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3T

Reference : PE 6001M



Item name	DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3T
EAN code	3701555307121
Intro	Especially adapted to painting, bodywork and brake and tyre service activities. Installation possibilities: floor-standing or floor built-in.
Text	Ease of access: 100mm high lowered floor passage, lockable access ramps for extended lifting platforms Up and down control by push buttons on control console Powerful lift: Extended mechanical tilt lever system, for full power lift at the lowest point 100mm Working comfort: scissors control by double hydraulic master-slave system; synchronization control by photocell.
Specifications	Specifications: <ul style="list-style-type: none">- lifting height : 100-1950mm- lifting time : +/- 40s- lowering time: +/- 35s- width/length of tracks: 650/1420-2000mm- system synchronization: photo cell- width/length of floor required for installation: 2000/2030mm- drive power: 2.2kW- drive voltage: (3 ~) 400/50 V/Hz- concrete strength/quality: 200mm-C20/25- maximum safety: double hydraulic safety system (without mechanical lock and

compressed air), emergency lowering system in case of power failure, anti-crushing intermediate stop according to CE standards and sound signal
- made in Europe

Advice

Installation et mise en service, nous consulter.
Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Tension 240V

Product weight 840.00 kg

Maximum load (T) 3.00 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 6001M-1 - DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3T PACK. 1/2
1 x PE 6001M-2 - DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3T PACK. 2/2



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)