

SCISSOR LIFT DUAL CYLINDER LOW RAISE 230V 3T

Reference : PE 6002M



Item name	SCISSOR LIFT DUAL CYLINDER LOW RAISE 230V 3T
Bar code	3701555307107
Introduction	Especially adapted to painting, bodywork and brake and tyre service activities. Installation possibilities: floor-standing or floor built-in.
Text	 Ease of access: 105mm high lowered floor passage, lockable access ramps for extended lifting platforms. Up and down control by push buttons on control box. Working comfort: scissor control by double hydraulic master-slave system, synchronisation control by photocell, adjustable ramp spacing from 700 to 900mm, suitable for micro cars, vans and utility vehicles. Powerful lift: extended mechanical tilt lever system, for full power lift at the lowest point 105mm.
Product highlight	Ideal for small cars
Specifications	 Specifications: lifting height : 105-960mm lifting time: +/- 20s lowering time: +/- 20s track width/length: 530/1450-2036mm system synchronization: photocell drive power: 2.2kw drive voltage: (3 ~) 400/50 V/Hz maximum safety: double hydraulic safety system (without mechanical lock and

Advice	 compressed air), emergency lowering system in case of power failure, anti-crushing intermediate stop according to CE standards and sound signal made in Europe Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	240V
Product weight (kg)	610.00 kg
Maximum load (T)	3.00 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6002M-1 - SCISSOR LIFT DUAL CYLINDER LOW RAISE 230V 3T PACK. 1/2 1 x PE 6002M-2 - SCISSOR LIFT DUAL CYLINDER LOW RAISE 230V 3T PACK.
	2/2

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France

TE

Tel : +33 (0) 4 79 72 62 22 Fax : Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)