

## DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T

Reference : PE 6004M



|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Item name</b>      | DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>EAN code</b>       | 3701555307145                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Intro</b>          | Especially adapted to painting, bodywork and brake and tyre service activities.<br>Installation possibilities: floor-standing or floor built-in.                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Text</b>           | Ease of access: 105mm high lowered floor passage, lockable access ramps for extended lifting platforms.<br>Up and down control by push buttons on control console.<br>Powerful lift: Extended mechanical tilt lever system, for full power lift at the lowest point 105mm.<br>Working comfort & maximum safety: scissors control by double hydraulic safety master-slave system (without mechanical detent or compressed air) synchronization control by photocell, emergency lowering system in case of power failure, intermediate anti-crushing stop to CE standards and audible signal.<br>European origin. |
| <b>Specifications</b> | Specifications: <ul style="list-style-type: none"><li>- lifting height : 105-1950mm</li><li>- lifting time : +/- 40s</li><li>- lowering time: +/- 35s</li><li>- track width/length: 650/1420-2000mm</li><li>- system synchronization: photo cell</li><li>- control console</li><li>- width/length of floor required for installation: 2000/2030mm</li></ul>                                                                                                                                                                                                                                                     |

- drive power: 2.2kw
- Drive voltage: (3 ~) 400/50V/Hz
- concrete strength/quality: 200mm-C20/25
- Emergency lowering system in case of power failure, anti-crushing intermediate stop according to CE standards and sound signal
- made in Europe

**Advice** Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

|                                    |                                                                                                                                                  |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Warranty period</b>             | 2 years                                                                                                                                          |
| <b>Power</b>                       | 2200W                                                                                                                                            |
| <b>Tension</b>                     | 240V                                                                                                                                             |
| <b>Length</b>                      | 2,270.00 mm                                                                                                                                      |
| <b>Width</b>                       | 2,130.00 mm                                                                                                                                      |
| <b>Product weight</b>              | 860.00 kg                                                                                                                                        |
| <b>Max. height</b>                 | 1,950.00 mm                                                                                                                                      |
| <b>Maximum load (T)</b>            | 3.50 T                                                                                                                                           |
| <b>Tariff code</b>                 | Tariff Equipment (TE)                                                                                                                            |
| <b>Composition of nomenclature</b> | 1 x PE 6004M-1 - DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T PACK. 1/2<br>1 x PE 6004M-2 - DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T PACK. 2/2 |



**\*Public price Exl. Tax : €7,900.00**

\*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS  
 83, chemin de la CROUZA  
 73800 CHIGNIN  
 France

Tel : +33 (0) 4 79 72 62 22  
 Fax :

Monday to Friday - From 8 to  
 12h30 and from 14h to 17h30  
 (16h30 on Friday)