

SMOKE LEAK DETECTOR

Reference: AC 0411BL



Item name SMOKE LEAK DETECTOR

Bar code 3701555311432

Text Thanks to its compact size, this machine is easily transportable, allowing intervention in

the entire workshop.

Its integrated compressor eliminates the need for an air supply.

Compatible with the majority of the fleet, connected to the battery terminals, it allows

quick diagnosis of the vehicle's closed circuits (turbo, exhaust, cooling, etc.).

To detect micro leaks on the circuits:

- vacuum (excluding EVAP valve, components and diaphragm not resistant to 1bar pressure)
- exhaust
- turbo insulation (excluding pneumatic Wasgate, may entail certain risks 1bar pressure)
- oil pan
- admission
- cooling

This device considerably reduces leak detection time by diffusing an opaque, fine and

instantly identifiable smoke on even the smallest leaks.

Without any risk for the user and the vehicle.

Product highlight

Perfect for occasional use!

Specifications

Specifications:

- power supply: 12V

- output pressure: 1.2 bar for turbo system

- flow rate: 8L/min - smoke control

- mode of operation: air only or smoke

- control manometer - oil capacity: 50ml - mineral oil (included)

- supplied with its accessories

- test fluid 250 ml = 35 hours of use

- weight: 3,7Kg

- dimensions: 180x125x210mm

Contents Contents:

- main unit

- accessory case - adapter cone

- power cable

- smoke distribution pipe

- funnel

- universal inflatable stopper - pouch replacement rubber

- test fluid (250 ml)

- oil filler cap adapter (for most BMW vehicles)

- smoke diffuser

- set of blanking plugs

Warranty period 2 years

Voltage 12V

More Use oiler

Product weight (kg) 4.50 kg

Capacity (ml) 50.00 ml

Capacity (1) 0.051

Tariff code Tariff Normal (TN)

Product range B-Line

Warranty Procedure DIAGNOSTIC













CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France

Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)