

4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T

Reference : PE 4101T



| | |
|--------------------------|---|
| Item name | 4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T |
| Bar code | 3701555318059 |
| Text | <p>Electro-hydraulic Post lift ideally designed for geometry and technical control, with manual swash plates and optional turntable slots.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles, motorhomes and construction equipment.</p> <p>Working comfort: One-piece access ramps, quick and easy vehicle positioning.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars. PE 4103.</p> |
| Product highlight | equipped with an air supply under the rails |
| Specifications | <p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 220-1850mm- lifting time: +/- 50s- lowering time: +/- 30s- track width/length: 610/5160mm- adjustable distance between runways: 820/920mm- air supply 8bar- drive power: 3kW- drive voltage: (3 ~) 400V/50 V/Hz- maximum safety: single-cylinder lifting, synchronization driven by 4 cables |

- pneumatic release of safety catches
- safety system in case of cable breakage,
- emergency lowering system in the event of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet with pneumatic connector in the middle of one of the interior platforms, under the rails
- engine protection
- 230V electrical socket on electrical box
- manual turntables
- Epoxy paint

| | |
|--|--|
| Options | PE 7100 PE 0104 |
| Advice | Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus. |
| Warranty period | 2 years |
| Power | 3000W |
| Voltage | 400V |
| Width | 3,185.00 mm |
| Height | 2,350.00 mm |
| Max. height | 1,850.00 mm |
| Min. height | 220.00 mm |
| Drive through width | 2,830.00 mm |
| Maximum load (T) | 5.00 T |
| Tariff code | Tariff Equipment (TE) |
| Composition of nomenclature | 1 x PE 4101T-1 - 4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5T 1/1 4 x SA 3012 - HV46 HYDRAULIC OIL 5L |
| Warranty Procedure | INTERVENTION |
| Customer benefit | Supplied with HV46 hydraulic oil and ground fixing kit |
| Pneumatic power supply required | YES |
| Circuit breaker/Cable section | 16A D / 5x2.5mm ² |
| Soil quality | >20cm Béton C20/25 |

2
WARRANTY


400V



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)