

4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T

Reference : PE 4101T



Item name	4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T
Bar code	3701555318059
Text	<p>Electro-hydraulic Post lift ideally designed for geometry and technical control, with manual swash plates and optional turntable slots.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles, motorhomes and construction equipment.</p> <p>Working comfort: One-piece access ramps, quick and easy vehicle positioning.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars. PE 4103.</p>
Product highlight	equipped with an air supply under the rails
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 220-1850mm- lifting time: +/- 50s- lowering time: +/- 30s- track width/length: 610/5160mm- adjustable distance between runways: 820/920mm- air supply 8bar- drive power: 3kW- drive voltage: (3 ~) 400V/50 V/Hz- maximum safety: single-cylinder lifting, synchronization driven by 4 cables

- pneumatic release of safety catches
- safety system in case of cable breakage,
- emergency lowering system in the event of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet with pneumatic connector in the middle of one of the interior platforms, under the rails
- engine protection
- 230V electrical socket on electrical box
- manual turntables
- Epoxy paint

Options PE 7100
PE 0104

Advice Installation et mise en service, nous consulter.
Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
Frais de transport non inclus.

Warranty period 2 years

Power 3000W

Voltage 400V

Width 3,185.00 mm

Height 2,350.00 mm

Max. height 1,850.00 mm

Min. height 220.00 mm

Drive through width 2,830.00 mm

Maximum load (T) 5.00 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 4101T-1 - 4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5T
1/1
4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Circuit breaker/Cable section 16A D / 5x2.5mm²



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)