

## 4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T

Reference : PE 4101T



<b>Item name</b>	4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T
<b>EAN code</b>	3701555318059
<b>Text</b>	<p>Electro-hydraulic Post lift ideally designed for geometry and technical control, with manual swash plates and optional turntable slots.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles, motorhomes and construction equipment.</p> <p>Working comfort: One-piece access ramps, quick and easy vehicle positioning.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160m long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars. PE 4103.</p>
<b>Product highlight</b>	equipped with an air supply under the rails
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 220-1850mm</li><li>- lifting time: +/- 50s</li><li>- lowering time: +/- 30s</li><li>- track width/length: 610/5160mm</li><li>- adjustable distance between runways: 820/920mm</li><li>- air supply 8bar</li><li>- drive power: 3kW</li><li>- drive voltage: (3 ~) 400V/50 V/Hz</li><li>- maximum safety: single-cylinder lifting, synchronization driven by 4 cables</li></ul>

- pneumatic release of safety catches
- safety system in case of cable breakage,
- emergency lowering system in the event of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet with pneumatic connector in the middle of one of the interior platforms, under the rails
- engine protection
- 230V electrical socket on electrical box
- manual turntables
- Epoxy paint

**Options** PE 7100  
PE 0104

**Advice** Installation et mise en service, nous consulter.  
Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
Frais de transport non inclus.

**Warranty period** 2 years

**Power** 3000W

**Tension** 400V

**Width** 3,185.00 mm

**Height** 2,350.00 mm

**Max. height** 1,850.00 mm

**Min. height** 220.00 mm

**Drive through width** 2,830.00 mm

**Maximum load (T)** 5.00 T

**Tariff code** Tariff Equipment (TE)

**Composition of nomenclature** 1 x PE 4101T-1 - 4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5T  
1/1  
4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

**Warranty Procedure** INTERVENTION

**Customer benefit** Supplied with HV46 hydraulic oil and ground fixing kit

**Disjoncteur/Section de câble** 16A D / 5x2.5mm<sup>2</sup>



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to  
12h30 and from 14h to 17h30  
(16h30 on Friday)