

4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T

Reference: PE 4102T



Item name 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T

Bar code 3701555318097

Text Suitable for mechanical work, light commercial vehicles, camper vans, construction

equipment, ideally designed for geometry with manual swash plates and optional turntable

slots.

4T auxiliary lifts with double galvanized extensions.

Suitable for mechanical work, passenger cars, light commercial vehicles, camper vans and

construction equipment.

Work comfort: access platforms equipped with auxiliary lift.

Fast, easy positioning of low-clearance vehicles, for rapid repair or inspection, 5160mm

long tracks.

Optional parking kit for 2 cars. PE 4103.

Product highlight 5T auxiliary lifts with double galvanized extensions

Specifications Specifications:

- lifting height: 220-1850mm

- lifting time: +/- 50s - lowering time: +/- 30s

- track width/length: 500/5160mm

- adjustable distance between runways: 910-1010mm

- required air supply 6-8 bar.

- drive power: 3kW

- drive voltage: $(3 \sim) 400/50 \text{ V/Hz}$

- maximum safety: single-cylinder lifting, synchronization driven by 4 cables
- pneumatic release of safety catches
- auxiliary lifts 5T capacity
- safety system in case of cable breakage,
- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet under railsengine protection
- 230V power socket on electric box
- pneumatic swashplates

- Epoxy paint

Advice Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par

un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 3000W

Voltage 400V

Width 3,185.00 mm

Height 2,350.00 mm

Max. height 1,850.00 mm

Min. height 220.00 mm

Drive through width 2,830.00 mm

Maximum load (T) 5.00 T

Tariff code Tariff Equipment (TE)

Composition of 1 x PE 4102T-1 - 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 1/1

nomenclature 4 x SA 3012 - HV46 HYDRAULIC OIL 5L

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power YES

supply required

Circuit 16A D / 5x2.5mm2

breaker/Cable

section

Soil quality >20cm Béton C20/25









CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France

Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on

Friday)