

## 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T

Reference : PE 4102T



<b>Item name</b>	4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T
<b>Bar code</b>	3701555318097
<b>Text</b>	<p>Suitable for mechanical work, light commercial vehicles, camper vans, construction equipment, ideally designed for geometry with manual swash plates and optional turntable slots.</p> <p>4T auxiliary lifts with double galvanized extensions.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles, camper vans and construction equipment.</p> <p>Work comfort: access platforms equipped with auxiliary lift.</p> <p>Fast, easy positioning of low-clearance vehicles, for rapid repair or inspection, 5160mm long tracks.</p> <p>Optional parking kit for 2 cars. PE 4103.</p>
<b>Product highlight</b>	5T auxiliary lifts with double galvanized extensions
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 220-1850mm</li><li>- lifting time: +/- 50s</li><li>- lowering time: +/- 30s</li><li>- track width/length: 500/5160mm</li><li>- adjustable distance between runways: 910-1010mm</li><li>- required air supply 6-8 bar.</li><li>- drive power: 3kW</li><li>- drive voltage: (3 ~) 400/50 V/Hz</li></ul>

- maximum safety: single-cylinder lifting, synchronization driven by 4 cables
- pneumatic release of safety catches
- auxiliary lifts 5T capacity
- safety system in case of cable breakage,
- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet under rails
- engine protection
- 230V power socket on electric box
- pneumatic swashplates
- Epoxy paint

**Advice** Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

**Warranty period** 2 years  
**Power** 3000W  
**Voltage** 400V  
**Width** 3,185.00 mm  
**Height** 2,350.00 mm  
**Max. height** 1,850.00 mm  
**Min. height** 220.00 mm  
**Drive through width** 2,830.00 mm

**Maximum load (T)** 5.00 T

**Tariff code** Tariff Equipment (TE)

**Composition of nomenclature** 1 x PE 4102T-1 - 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 1/1  
 4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

**Warranty Procedure** INTERVENTION

**Customer benefit** Supplied with HV46 hydraulic oil and ground fixing kit

**Circuit breaker/Cable section** 16A D / 5x2.5mm<sup>2</sup>



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)