

## 2 COLUMNS POST LIFT HIGH PASSAGE 5.00m 400V 6T 4 ARTICULATED ARMS

Reference : PE 2350T



<b>Item name</b>	2 COLUMNS POST LIFT HIGH PASSAGE 5.00m 400V 6T 4 ARTICULATED ARMS
<b>EAN code</b>	3701555318042
<b>Text</b>	<p>Particularly adapted to repair activities on extended utility vehicles, 4x4, micro car. Electro-hydraulic post lift. Pusher cylinder direct on carriage. Arms with adjustable joints. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning. Hydraulic power pack: equipped with a position safety device for precise intervention, gearbox assembly, nut alignment, etc. Multiple lifting capacities thanks to 4 multi-adjustable articulated arms. Cylinder and cable protection strip included on each column.</p>
<b>Product highlight</b>	<p>6T capacity Multi-position arm</p>
<b>Specifications</b>	<p>Specifications: - lifting height: 95-1850mm - lifting time: +/- 50s - lowering time: +/- 30s - drive power: 2.2kW - drive voltage: 400V/50 V/Hz</p>

- concrete strength/quality: 200mm-C20/25
- adjustable screw buffers, stroke 70-140mm
- electrical release of safety catches
- emergency lowering system in the event of power failure
- system synchronization: by cable
- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal
- engine protection
- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder and cables included on each column
- supplied with 4x70mm risers and brackets
- Epoxy paint

**Advice**

Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

<b>Warranty period</b>	2 years
<b>Power</b>	2200W
<b>Tension</b>	400V
<b>Length</b>	4,000.00 mm
<b>Height</b>	5,000.00 mm
<b>Max. height</b>	1,850.00 mm
<b>Min. height</b>	95.00 mm
<b>Drive through width</b>	3,190.00 mm
<b>Maximum load (T)</b>	6.00 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 2340 - 2 COLUMNS HIGH PASSAGE 400V 6T WITHOUT ARMS 1 x PE 2355T - ENGINE BLOC 2 COLUMNS POST LIFT 6T 1 x PE 2341 - PAIR OF ARTICULATED ARMS FOR 6T 1 x PE 2343 - HIGH PASSAGE EXTENSION 5m00 FOR 6T 2 x <a href="#">SA 3012 - HV46 HYDRAULIC OIL 5L</a>

**Warranty Procedure** INTERVENTION

**Customer benefit** Delivered with 46V hydraulic oil

**Disjoncteur/Section de câble** 10A D / 5x2.5mm<sup>2</sup>



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to  
12h30 and from 14h to 17h30  
(16h30 on Friday)