

## DOUBLE SCISSOR LIFT 400V 3.6T LOW PROFILE ON/IN-GROUND

Reference : PE 6236T



<b>Item name</b>	DOUBLE SCISSOR LIFT 400V 3.6T LOW PROFILE ON/IN-GROUND
<b>Bar code</b>	3701555318073
<b>Text</b>	<p>Especially adapted to painting, bodywork and brake and tyre service activities. Installation possibilities: in or on ground. Easy access: 110mm lowered floor clearance, lockable access ramps to extend platforms. Maximum comfort and safety: double hydraulic master-slave safety system, combined with a rack and pinion system, to maintain the lift in position for long periods.</p>
<b>Product highlight</b>	For free-standing or built-in use
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 110-1880mm</li><li>- lifting time: +/- 50s</li><li>- lowering time: +/- 30s</li><li>- track width/length: 630/1480-2090mm</li><li>- system synchronization: photo cell</li><li>- air supply required 6-8 bar.</li><li>- control console</li><li>- drive power: 3kw</li><li>- drive voltage: (3 ~ + N) 400V/50/Hz</li><li>- emergency lowering system in case of power failure</li><li>- intermediate stop at 20 cm from the ground for operator safety and anti-crushing audible signal</li></ul>
<b>Advice</b>	

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

<b>Warranty period</b>	2 years
<b>Power</b>	3000W
<b>Voltage</b>	400V
<b>Length (mm)</b>	2,090.00 mm
<b>Width</b>	2,110.00 mm
<b>Max. height</b>	1,880.00 mm
<b>Min. height</b>	110.00 mm
<b>Maximum load (T)</b>	3.60 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 6236T-1 - DOUBLE SCISSOR LIFT 2CYLINDER 400V 3.6T LOW PROFILE ON/IN-GROUND 1/3 1 x PE 6236T-2 - DOUBLE SCISSOR LIFT 2CYLINDER 400V 3.6T LOW PROFILE ON/IN-GROUND 2/3 1 x PE 6236T-3 - DOUBLE SCISSOR LIFT 2CYLINDER 400V 3.6T LOW PROFILE ON/IN-GROUND 3/3 3 x <a href="#">SA 3012 - HV46 HYDRAULIC OIL 5L</a>

#### Warranty ProcedureINTERVENTION

<b>Customer benefit</b>	Supplied with HV46 hydraulic oil and ground fixing kit
<b>Pneumatic power supply required</b>	YES
<b>Circuit breaker/Cable section</b>	16A D / 5x2.5mm <sup>2</sup>
<b>Soil quality</b>	>20cm Béton C20/25
<b>After-sales videos</b>	Cliquez sur l'opération qui vous intéresse pour voir la <b>vidéo</b> :



[PURGE ET SYNCHRONISATION DES VERINS](#)

**\*Public price Exl. Tax : €5,799.00**

\*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)