

DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 4T IN-GROUND

Reference : PE 6340T



Item name	DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 4T IN-GROUND
Bar code	3701555318110
Text	<p>Particularly suitable for 4x4s and SUVs. In-ground. Maximum comfort and safety: controlled by a double hydraulic master-slave safety system combined with a rack and pinion system to maintain a lasting position. Galvanized 2-extension platforms.</p>
Product highlight	SUV and 4X4 special
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 0-1999mm- lifting time: +/- 50s- lowering time: +/- 30s- track width/length: 565/1660-2060mm- system synchronization: photo cell- air supply required 6-8 bar.- control console- drive power: 3kw- drive voltage: (3 ~) 400V/50 V/Hz- emergency lowering system in case of power failure- intermediate stop at 20 cm from the ground for operator safety and anti-crushing audible signal
Advice	

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period	2 years
Power	3000W
Voltage	400V
Max. height	2,120.00 mm
Maximum load (T)	4.00 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6340T-1 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 4T IN-GROUND 1/4 1 x PE 6340T-2 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 4T IN-GROUND 2/4 1 x PE 6340T-3 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 4T IN-GROUND 3/4 1 x PE 6340T-4 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 4T IN-GROUND 4/4 3 x SA 3012 - HV46 HYDRAULIC OIL 5L

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required YES

Circuit breaker/Cable section 16A D / 5x2.5mm²

on-ground/in-ground in-ground

Soil quality >20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)