

EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T IN-GROUND

Reference : PE 6351T



Item name	EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T IN-GROUND
Bar code	3701555318127
Text	Especially adapted for technical inspection, geometries, repair and adjustment of headlights. Installation possibilities: floor-standing or floor built-in for LV and LCV. Working comfort: quick and easy vehicle mounting on the extra-low 140mm lift. Maximum safety: mechanical safety rack on main and auxiliary scissors to stabilize position. Auxiliary lift capacity 4.5T with 2 galvanized extensions. The secondary auxiliary cylinder is chrome-plated for extra durability. Pneumatically locked swing plates.
Product highlight	perfect drivetrain control
Specifications	Specifications: - lifting height: 0-1980mm - lifting time: +/- 50s - lowering time: +/- 30s - track width/length: 690/5200mm - system synchronization: photo cell - control console - drive power: 3kw - drive voltage: (3 ~) 400V/50 V/Hz

Advice	 required air supply 6-8 bar. swing tracks pneumatic locking epoxy paint emergency lowering system in case of power failure intermediate stop at 20 cm from the ground for operator safety and anti-crushing audible signal Installation et mise en service, nous consulter.
	Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	3000W
Voltage	400V
Length (mm)	5,200.00 mm
Max. height	1,950.00 mm
Maximum load (T)	5.50 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6351T-1 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN- GROUND 1/4 1 x PE 6351T-2 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 45T IN- GROUND 2/4 1 x PE 6351T-3 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN- GROUND 3/4 1 x PE 6351T-4 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN- GROUND 4/4 4 x <u>SA 3012 - HV46 HYDRAULIC OIL 5L</u>
Warranty Procedure INTERVENTION	
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES

Circuit 16A D / 5x2.5mm2 breaker/Cable section

on-ground/in-ground in-ground

Soil quality >20cm Béton C20/25



*Public price Exl. Tax : €15,999.00

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel : +33 (0) 4 79 72 62 22 Fax : Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)