

2 COLUMNS POST LIFT HIGH PASSAGE 4.50m 400V 4T 4 ARMS FOR EV

Reference : PE 2246T



Item name	2 COLUMNS POST LIFT HIGH PASSAGE 4.50m 400V 4T 4 ARMS FOR EV
Bar code	3701555318189
Text	<p>Electro-hydraulic post lift. Pusher direct cylinder on cart. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning. Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 VE 3-stage arms.</p>
Product highlight	Free movement between columns
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 95-1990mm- lifting time: +/- 50s- lowering time: +/- 30s- drive power: 2.2kW- drive voltage: 400V/50 V/Hz- adjustable screw buffers, stroke 70-140mm- electrical release of safety catches- emergency lowering system in case of power failure- system synchronization: by cable- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal- engine protection

- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder and cables included on each column
- supplied with 4x70mm risers and brackets
- Epoxy paint

Advice Installation et mise en service, nous consulter.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440.00 mm
Width	44.00 mm
Height	4,600.00 mm
Max. height	1,990.00 mm
Min. height	95.00 mm
Drive through width	2,600.00 mm
Maximum load (T)	4.00 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2200 - 2 COLUMNS HIGH PASSAGE 400V 4T WITHOUT ARMS 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T 2 x PE 2113 - PAIR OF ARTICULATED ARMS FOOT PROTECTION 1.26m 1 x PE 2202 - HIGH PASSAGE EXTENSION AND ACCESSORIES 4T 4m50 2 x SA 3012 - HV46 HYDRAULIC OIL 5L

Warranty Procedure INTERVENTION

Customer benefit	Delivered with 46V hydraulic oil
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D / 5x2.5mm ²
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)