

2 COLUMNS SYMETRIC POST LIFT WITH BASEMENT 400V 4T 4 ARMS 1.50m

Reference : PE 2105T



Item name	2 COLUMNS SYMETRIC POST LIFT WITH BASEMENT 400V 4T 4 ARMS 1.50m
Bar code	3701555318141
Text	<p>A post lift designed to facilitate column installation and alignment thanks to its 40mm-thick base.</p> <p>With the PE 2101 option, it can be used for screeds that do not meet the minimum thickness requirement of 200mm (it can cover up to 150mm), or that present a slight flatness problem.</p> <p>Electro-hydraulic post lift.</p> <p>Pusher cylinder on cable.</p> <p>Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 x 1500mm 3-stage arms.</p>
Product highlight	Low-thickness passage
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 100-2100mm- lifting time: +/- 50s- lowering time: +/- 30s- drive power: 2.2kW- drive voltage: (3 ~ + N) 400V/50/Hz- adjustable screw buffers, stroke 70-140mm- automatic release of safety catches- emergency lowering system in case of power failure

- system synchronization: by cable
- intermediate stop 20cm above ground for user safety and anti-crushing audible signal
- engine protection
- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder, chain and cables included on each column
- supplied with 4 x 70mm risers and brackets
- Epoxy paint

Advice Installation et mise en service, nous consulter.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period 2 years
Power 2200W
Voltage 400V
Length (mm) 3,440.00 mm
Width 44.00 mm
Height 2,965.00 mm
Max. height 2,100.00 mm
Min. height 100.00 mm
Drive through width 2,460.00 mm

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 2102 - 2 COLUMNS WITH BASEMENT 400V 4T WITHOUT ARMS
 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T
 1 x PE 2104 - 2 COLUMNS POST LIFT WITH BASEMENT ACCESSORIES 4T
 2 x [PE 2111 - PAIR OF ARMS WITH BLOCK 1.50m AND FOOT PROTECTION](#)
 2 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)
 1 x [PE 2117 - 2 COLUMNS POST LIFT BASE 4T LOW PASSAGE](#)

Warranty Procedure INTERVENTION

Customer benefit Delivered with 46V hydraulic oil

Pneumatic power supply required NO

Circuit breaker/Cable section 10A D / 5x2.5mm²

Soil quality >20cm Béton C20/25

2
WARRANTY

2200
W


400V



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)