

2 COLUMNS SYMETRIC POST LIFT WITH BASEMENT 400V 4T 4 ARMS 1.50m

Reference : PE 2105T



Item name	2 COLUMNS SYMETRIC POST LIFT WITH BASEMENT 400V 4T 4 ARMS 1.50m
Bar code	3701555318141
Text	A post lift designed to facilitate column installation and alignment thanks to its 40mm- thick base. With the PE 2101 option, it can be used for screeds that do not meet the minimum thickness requirement of 200mm (it can cover up to 150mm), or that present a slight flatness problem. Electro-hydraulic post lift. Pusher cylinder on cable. Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 x 1500mm 3-stage arms.
Product highlight	Low-thickness passage
Specifications	 Specifications: lifting height: 100-2100mm lifting time: +/- 50s lowering time: +/- 30s drive power: 2.2kW drive voltage: (3 ~ + N) 400V/50/Hz adjustable screw buffers, stroke 70-140mm automatic release of safety catches emergency lowering system in case of power failure

Advice	 system synchronization: by cable intermediate stop 20cm above ground for user safety and anti-crushing audible signal engine protection door protection on columns 230V electrical socket on electrical box protective strip for cylinder, chain and cables included on each column supplied with 4 x 70mm risers and brackets Epoxy paint Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440.00 mm
Width	44.00 mm
Height	2,965.00 mm
Max. height	2,100.00 mm
Min. height	100.00 mm
Drive through width 2,460.00 mm	
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2102 - 2 COLUMNS WITH BASEMENT 400V 4T WITHOUT ARMS 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T 1 x PE 2104 - 2 COLUMNS POST LIFT WITH BASEMENT ACCESSORIES 4T 2 x PE 2111 - PAIR OF ARMS WITH BLOCK 1.50m AND FOOT PROTECTION 2 x SA 3012 - HV46 HYDRAULIC OIL 5L 1 x PE 2117 - 2 COLUMNS POST LIFT BASE 4T LOW PASSAGE
Warranty Procedure INTERVENTION	
Customer benefit	Delivered with 46V hydraulic oil
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D / 5x2.5mm2

Soil quality >20cm Béton C20/25



*Public price Exl. Tax : €4,199.00

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel : +33 (0) 4 79 72 62 22 Fax : Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)