

## 2 COLUMNS SYMETRIC POST LIFT WITH BASEMENT 400V 4T 4 ARMS 1.80m

Reference : PE 2106T



<b>Item name</b>	2 COLUMNS SYMETRIC POST LIFT WITH BASEMENT 400V 4T 4 ARMS 1.80m
<b>EAN code</b>	3701555318158
<b>Text</b>	<p>A post lift designed to facilitate installation and alignment of the columns using the baseplate.</p> <p>With the PE 2101 option, it can be used for screeds that do not meet the minimum thickness requirement of 200mm, or that present a slight flatness problem.</p> <p>Electro-hydraulic post lift.</p> <p>Pusher cylinder on cable.</p> <p>Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 x 1800mm 3-stage arms.</p>
<b>Product highlight</b>	Low-thickness passage
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 100-2100mm</li><li>- lifting time: +/- 50s</li><li>- lowering time: +/- 30s</li><li>- drive power: 2.2kW</li><li>- drive voltage: (3 ~ + N) 400V/50/Hz</li><li>- adjustable screw buffers, stroke 70-140mm</li><li>- automatic release of safety catches</li><li>- emergency lowering system in the event of power failure</li><li>- system synchronization: by cable</li></ul>

- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal
- engine protection
- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder, chain and cables included on each column
- supplied with 4x70mm risers and brackets
- Epoxy paint

**Advice** Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

**Warranty period** 2 years  
**Power** 2200W  
**Tension** 400V  
**Length** 3,440.00 mm  
**Width** 44.00 mm  
**Height** 2,965.00 mm  
**Max. height** 2,100.00 mm  
**Min. height** 100.00 mm  
**Drive through width** 2,460.00 mm

**Tariff code** Tariff Equipment (TE)

**Composition of nomenclature** 1 x PE 2102 - 2 COLUMNS WITH BASEMENT 400V 4T WITHOUT ARMS  
 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T  
 1 x PE 2104 - 2 COLUMNS POST LIFT WITH BASEMENT ACCESSORIES 4T  
 2 x [PE 2112 - PAIR OF ARMS WITH BLOCK 1.80m AND FOOT PROTECTION](#)  
 2 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)  
 1 x [PE 2117 - 2 COLUMNS POST LIFT BASE 4T LOW PASSAGE](#)

**Warranty Procedure** INTERVENTION

**Customer benefit** Delivered with 46V hydraulic oil

**Disjoncteur/Section de câble** 10A D / 5x2.5mm<sup>2</sup>



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)