

## 2 COLUMNS POST LIFT HIGH PASSAGE 3.80m 400V 4T 4 ARMS 1.80m

Reference : PE 2240T



<b>Item name</b>	2 COLUMNS POST LIFT HIGH PASSAGE 3.80m 400V 4T 4 ARMS 1.80m
<b>EAN code</b>	3701555318165
<b>Text</b>	<p>Electro-hydraulic post lift. Pusher direct cylinder on cart. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, etc.), facilitating workshop cleaning. Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 x 1800mm 3-stage arms.</p>
<b>Product highlight</b>	Free movement between columns
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 95-1990mm</li><li>- lifting time: +/- 50s</li><li>- lowering time: +/- 30s</li><li>- drive power: 2.2kW</li><li>- drive voltage: 400V/50 V/Hz</li><li>- adjustable screw buffers, stroke 70-140mm</li><li>- electrical release of safety catches</li><li>- emergency lowering system in case of power failure</li><li>- system synchronization: by cable</li><li>- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal</li><li>- engine protection</li></ul>

- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder and cables included on each column
- supplied with 4x70mm risers and brackets
- epoxy paint

**Advice**

Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

<b>Warranty period</b>	2 years
<b>Power</b>	2200W
<b>Tension</b>	400V
<b>Length</b>	3,440.00 mm
<b>Width</b>	44.00 mm
<b>Height</b>	3,900.00 mm
<b>Max. height</b>	1,990.00 mm
<b>Min. height</b>	95.00 mm
<b>Drive through width</b>	2,600.00 mm
<b>Maximum load (T)</b>	4.00 T
<b>Tariff code</b>	Tariff Equipment (TE)

**Composition of nomenclature**

- 1 x PE 2200 - 2 COLUMNS HIGH PASSAGE 400V 4T WITHOUT ARMS
- 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T
- 1 x PE 2204 - 2 COLUMNS POST LIFT HIGH PASSAGE 4T 3m80
- 2 x [PE 2112 - PAIR OF ARMS WITH BLOCK 1.80m AND FOOT PROTECTION](#)
- 2 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

**Warranty Procedure** INTERVENTION

**Customer benefit** Delivered with 46V hydraulic oil

