

2 COLUMNS POST LIFT HIGH PASSAGE 3.80m 400V 4T 4 ARMS FOR EV

Reference : PE 2241T



Item name	2 COLUMNS POST LIFT HIGH PASSAGE 3.80m 400V 4T 4 ARMS FOR EV
EAN code	3701555318172
Text	<p>Electro-hydraulic post lift. Pusher direct cylinder on cart. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning. Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 x 1500 mm 3-stage arms.</p>
Product highlight	Free movement between columns
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 95-1990mm- lifting time: +/- 50s- lowering time: +/- 30s- drive power: 2.2kW- drive voltage: 400V/50 V/Hz- adjustable screw buffers, stroke 70-140mm- electrical release of safety catches- emergency lowering system in case of power failure- system synchronization: by cable- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal- engine protection

- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder and cables included on each column
- supplied with 4x70mm risers and brackets
- Epoxy paint

Advice Installation et mise en service, nous consulter.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period	2 years
Power	2200W
Tension	400V
Length	3,440.00 mm
Width	44.00 mm
Height	3,900.00 mm
Max. height	1,990.00 mm
Min. height	95.00 mm
Drive through width	2,600.00 mm
Maximum load (T)	4.00 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2200 - 2 COLUMNS HIGH PASSAGE 400V 4T WITHOUT ARMS 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T 1 x PE 2204 - 2 COLUMNS POST LIFT HIGH PASSAGE 4T 3m80 2 x PE 2113 - PAIR OF ARTICULATED ARMS FOOT PROTECTION 1.26m 2 x SA 3012 - HV46 HYDRAULIC OIL 5L

Warranty Procedure INTERVENTION

Customer benefit Delivered with 46V hydraulic oil

