

2 COLUMNS POST LIFT HIGH PASSAGE 3.80m 400V 4T 4 ARMS FOR EV

Reference : PE 2241T



Item name	2 COLUMNS POST LIFT HIGH PASSAGE 3.80m 400V 4T 4 ARMS FOR EV
Bar code	3701555318172
Text	<p>Electro-hydraulic post lift. Pusher direct cylinder on cart. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning. Multiple lifting capacities thanks to telescopic arms in symmetrical version with 4 x 1500 mm 3-stage arms.</p>
Product highlight	Free movement between columns
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 95-1990mm- lifting time: +/- 50s- lowering time: +/- 30s- drive power: 2.2kW- drive voltage: 400V/50 V/Hz- adjustable screw buffers, stroke 70-140mm- electrical release of safety catches- emergency lowering system in case of power failure- system synchronization: by cable- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal- engine protection

- door protection on columns
- 230V electrical socket on electrical box
- protective strip for cylinder and cables included on each column
- supplied with 4x70mm risers and brackets
- Epoxy paint

Advice Installation et mise en service, nous consulter.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Voltage 400V

Length (mm) 3,440.00 mm

Width 44.00 mm

Height 3,900.00 mm

Max. height 1,990.00 mm

Min. height 95.00 mm

Drive through width 2,600.00 mm

Maximum load (T) 4.00 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 2200 - 2 COLUMNS HIGH PASSAGE 400V 4T WITHOUT ARMS
 1 x PE 2103T - ENGINE BLOC 2 COLUMNS POST LIFT 4T
 1 x PE 2204 - 2 COLUMNS POST LIFT HIGH PASSAGE 4T 3m80
 2 x [PE 2113 - PAIR OF ARTICULATED ARMS FOOT PROTECTION 1.26m](#)
 2 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

Warranty Procedure INTERVENTION

Customer benefit Delivered with 46V hydraulic oil

Pneumatic power supply required NO

Circuit breaker/Cable section 10A D / 5x2.5mm²

Soil quality >20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)