

## EXTRA LOW PROFILE SCISSOR LIFT AUXILIARY LIFT 400V 5T ON-GROUND

Reference: PE 6250T



Item name EXTRA LOW PROFILE SCISSOR LIFT AUXILIARY LIFT 400V 5T ON-GROUND

**Bar code** 3701555318080

**Text** Especially adapted for technical inspection, geometries, repair and adjustment of

headlights.

On ground scissor lift for LV and LCV.

Working comfort: quick and easy vehicle mounting on the extra-low 140mm post lift. Maximum safety: mechanical safety rack on main and auxiliary scissors to stabilize

position.

Auxiliary lift capacity 4T with 2 galvanized extensions.

The secondary auxiliary cylinder is chrome-plated for extra durability.

Pneumatically locked swing plates.

**Product highlight** Extra low-profile 140mm

**Specifications** Specifications:

- lifting height: 140-1850mm

- lifting time: +/- 50s - lowering time: +/- 30s

- track width/length: 655/5200mm

- total length with access ramps: 6600mm

- system synchronization: photo cell

control consoledrive power: 3kw

- drive voltage:  $(3 \sim) 400 \text{V}/50 \text{ V/Hz}$ 

- required air supply 6-8 bar. - swing tracks pneumatic locking

- epoxy paint

- emergency lowering system in case of power failure

- intermediate stop at 20 cm from the ground for operator safety and anti-crushing audible

signal

Advice Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par

un professionnel.

Frais de transport non inclus.

Warranty period

2 years

**Power** 

3000W

Voltage

400V

Length (mm)

5,000.00 mm

Width

2,190.00 mm

Max. height

1,850.00 mm

Min. height

140.00 mm

Maximum load (T) 5.00 T

Tariff code

Tariff Equipment (TE)

**Composition of** nomenclature

1 x PE 6250T-1 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-

GROUND 1/5

1 x PE 6250T-2 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-

GROUND 2/5

1 x PE 6250T-3 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-

GROUND 3/5

1 x PE 6250T-4 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-

GROUND 4/5

1 x PE 6250T-5 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-

GROUND 5/5

4 x SA 3012 - HV46 HYDRAULIC OIL 5L

Warranty Procedure INTERVENTION

**Customer benefit** Supplied with HV46 hydraulic oil and ground fixing kit

**Pneumatic power** supply required

YES

Circuit

16A D / 5x2.5mm2

breaker/Cable

section

on-ground/in-ground on-ground

Soil quality >20cm Béton C20/25











**CLAS EQUIPEMENTS** 83, chemin de la CROUZA 73800 CHIGNIN France

Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on

Friday)