

SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T TECH CONTROL IN-GROUND

Reference: PE 6352T



Item name SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T TECH CONTROL IN-GROUND

Bar code 3701555318134

Text Particularly suitable for technical inspections, geometries and repairs.

In ground scissor lift for light commercial vehicles.

Working comfort: quick and easy vehicle mounting on the extra-low 140mm lift. Maximum safety: mechanical safety rack on main and auxiliary scissors to stabilize

position.

Auxiliary lift capacity 4.5T with 2 galvanized extensions.

The secondary auxiliary cylinder is chrome-plated for extra durability. Supplied with 2 pneumatically-locked Swashplates and 2 shifting plates.

Supplied with 1 LCD screen console and a radio remote control for setting the shifting

plates in motion.

Product highlight perfect drivetrain control

Specifications Specifications:

lifting height: 0-1950mm
lifting time: +/- 50s
lowering time: +/- 30s

track width/length: 690/5700mmsystem synchronization: photo cell

control consoledrive power: 3kw

- drive voltage: $(3 \sim) 400 \text{V}/50 \text{ V/Hz}$

-required air supply 6-8 bar. -pneumatic oscillating tracks

- Epoxy paint

- emergency lowering system in case of power failure

- intermediate stop at 20 cm from the ground for operator safety and anti-crushing audible

signal

Advice Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par

un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 3000W

Voltage 400V

Width 5,700.00 mm

Max. height 1,950.00 mm

Maximum load (T) 5.50 T

Tariff code Tariff Equipment (TE)

Composition of

1 x PE 6352T-1 - SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T TECH CONTROL IN-

nomenclature GROUND 1/4

1 x PE 6352T-2 - SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T TECH CONTROL IN-

GROUND 2/4

1 x PE 6352T-3 - SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T TECH CONTROL IN-

GROUND 3/4

1 x PE 6352T-4 - SCISSOR LIFT 5.5T AUXILIARY LIFT 54.5T TECH CONTROL IN-

GROUND 4/4

4 x SA 3012 - HV46 HYDRAULIC OIL 5L

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power

supply required

16A D / 5x2.5mm2 Circuit

YES

breaker/Cable

section

on-ground/in-groundin-ground

Soil quality >20cm Béton C20/25











CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on

Friday)