

MOBILE GAS VACUUM

Reference : AG 0084



Item name MOBILE GAS VACUUM

Bar code 3701555318387

Introduction Ideal for moving to different work areas in car or motorcycle workshops

Text Trolley extractor mounted on 4 swivel wheels, height-adjustable, equipped with a Y and a 1.25m hose with exhaust nozzle and clamp, as well as a delivery sheath and storage console.

This equipment enables you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.

Specifications

Specifications:

- galvanized steel structure
- platform mounted on 4 swivel wheels for anti-tilt stability.
- epoxy paint (grey RAL 7040)
- 100 mm suction flange
- 1.25m of Ø100mm (-40° to +200°) high-temperature EPDM vulcanized fabric tubing.
- discharge: Ø 125mm length 10m
- power supply: 230V Mono
- motor power: 0.5hp, 0.37KW, 50HZ, 1.7A
- max flow: 250m³/h
- noise level: 66dB
- on/off switch
- exhaust nozzle equipped with anti-intrusion cloth, suction shut-off flap, for optimized suction on one mouth with access for Ø30mm opacimeter probe

Warranty period	2 years
Decibel level	66.00 dB
Voltage	240V
More	Products with electrical plug
Air flow rate	250
Tariff code	Tariff Equipment (TE)

Warranty Procedure INTERVENTION

Type of gas extraction system Mobile

DPF compatible NO

Hose diameter (mm) 100mm

Max. hose temperature (°C) 200°C



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)