

## MOBILE GAS VACUUM

Reference : AG 0084



**Item name** MOBILE GAS VACUUM

**Bar code** 3701555318387

**Introduction** Ideal for moving to different work areas in car or motorcycle workshops

**Text** Trolley extractor mounted on 4 swivel wheels, height-adjustable, equipped with a Y and a 1.25m hose with exhaust nozzle and clamp, as well as a delivery sheath and storage console.

This equipment enables you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.

### Specifications

Specifications:

- galvanized steel structure
- platform mounted on 4 swivel wheels for anti-tilt stability.
- epoxy paint (grey RAL 7040)
- 100 mm suction flange
- 1.25m of Ø100mm (-40° to +200°) high-temperature EPDM vulcanized fabric tubing.
- discharge: Ø 125mm length 10m
- power supply: 230V Mono
- motor power: 0.5hp, 0.37KW, 50HZ, 1.7A
- max flow: 250m<sup>3</sup>/h
- noise level: 66dB
- on/off switch
- exhaust nozzle equipped with anti-intrusion cloth, suction shut-off flap, for optimized suction on one mouth with access for Ø30mm opacimeter probe

<b>Warranty period</b>	2 years
<b>Decibel level</b>	66.00 dB
<b>Voltage</b>	240V
<b>More</b>	Products with electrical plug
<b>Air flow rate</b>	250
<b>Tariff code</b>	Tariff Equipment (TE)

#### **Warranty Procedure** INTERVENTION

**Type of gas extraction system** Mobile

**DPF compatible** NO

**Hose diameter (mm)** 100mm

**Max. hose temperature (°C)** 200°C



**\*Public price Exl. Tax : €2,199.00**

\*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)