

WHEEL BEARING PULLER MERCEDES VEHICLES

Reference : OM 3428



Item name	WHEEL BEARING PULLER MERCEDES VEHICLES
Bar code	3700461457333
Introduction	<p>Useful for secure, fast removal and replacement of wheel bearings directly on the vehicles.</p> <p>Housings are designed to offer perfect support on swivels and suitable suspension bushings for extraction and correct installation of bearings.</p> <p>Removal of support leg of shock absorber, removal of control arm and camber control is not needed anymore. Gain in time is around 1 hour.</p> <p>Extraction housings have notches which avoid removal of ABS sensors.</p>
Product highlight	Time-saver: avoids removal of ABS sensors
Contents	<p>Contents:</p> <ul style="list-style-type: none">- 2 housing rings- 1 housing: outside Ø104mm, inner Ø90mm-93mm, height 85mm- 1 housing with ABS notches: outside Ø104mm, inner Ø90-93mm, height 85mm- centering rings: 42-45-49-50-54-60-80mm- pressure rings: 66-70-73-75-79-83-84-85-87-88-90mm- extraction screw and M20 allen <p>Weight: 15kg</p>
Applications	<p>Traditional bearings from Ø66mm to Ø93mm</p> <p>Mercedes: 190(W201), Classe A (W168, W169), Classe B (W245, W124), Classe C (W202, W203), Classe E (W210), Classe M (W163, W164), Classe S (W639), Classe V (W639)</p>

Options Hydraulic extractor OM9384 is suggested for highly seized bearings.

Warranty period 2 years

Suitable for branded Mercedes vehicles

Tariff code Tariff Normal (TN)

Warranty ProcedureEASY



***Public price Exl. Tax : €465.00**

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)