

RIBBED PULLEY PULLER WITH INTERCHANGEABLE ARMS

Reference : OM 4067



Item name	RIBBED PULLEY PULLER WITH INTERCHANGEABLE ARMS
Bar code	3700461486227
Introduction	This tool allows to remove the crankshaft pulleys without damage. The adjustment of the claws is done by translation thanks to the worm screw for a better centering of the tool on the pulley. Reduced space required for motor intervention in place.
Product highlight	Interchangeable ball-locking arms
Specifications	Specifications: <ul style="list-style-type: none">- adjustable arms from Ø30 à 185mm- claw offset: 15mm- push screw length: 90mm- claw and push screw adjustment drive: 3/8" or hex 17mm- pulley groove thread: 3.56mm
Options	Option: <ul style="list-style-type: none">- SA4067: 32mm offset arms kit + L.180mm push screw
Warranty period	2 years
Tariff code	Tariff Normal (TN)
Product range	Approved by SNR
Warranty Procedure	EASY

2
WARRANTY



TN

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h30
and from 14h to 17h30 (16h30 on
Friday)