

## LOW PRESSURE COUPLER FOR GAS R1234yf

Reference : SA 4054



**Item name** LOW PRESSURE COUPLER FOR GAS R1234yf

**EAN code** 3700461456435

**Intro** This specific 3/8" coupler 3/8", according to the standard SAE J639, allows to refill or to detect an aircon gas leak R1234YF.  
It can be connected to the vehicle for maintenance purposes with great simplicity thanks to the quick-locking function.

**Text** The R1234 gas is dedicated to the new cars (class M1 and N1). The new European directive 2006/40/CE stipulates that all used refrigerants must have a GWP (Global Warning Potential) of less than 150.

**Warranty period** 2 years

**Tariff code** Tariff Normal (TN)

**Warranty Procedure** EASY

**Article(s) maître(s)** AC 1012 | AIR CONDITIONING LEAK DETECTION KIT  
AC 1014 | KIT AZOTE COMPLET DETECTION FUITES CLIMATISATION  
AC 1015 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)  
AC 1016 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)



TN

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h30  
and from 14h to 17h30 (16h30 on  
Friday)