

LOW PRESSURE COUPLER FOR GAS R1234yf

Reference : SA 4054



Item name LOW PRESSURE COUPLER FOR GAS R1234yf

EAN code 3700461456435

Intro This specific 3/8" coupler 3/8", according to the standard SAE J639, allows to refill or to detect an aircon gas leak R1234YF.
It can be connected to the vehicle for maintenance purposes with great simplicity thanks to the quick-locking function.

Text The R1234 gas is dedicated to the new cars (class M1 and N1). The new European directive 2006/40/CE stipulates that all used refrigerants must have a GWP (Global Warning Potential) of less than 150.

Warranty period 2 years

Tariff code Tariff Normal (TN)

Warranty Procedure EASY

Article(s) maître(s) AC 1012 | AIR CONDITIONING LEAK DETECTION KIT
AC 1014 | KIT AZOTE COMPLET DETECTION FUITES CLIMATISATION
AC 1015 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)
AC 1016 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)



TN

***Public price Exl. Tax : €87.00**

*Applicable user fees from 01/09/2024 to 31/08/2025

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)